

KCR



Equipped with:

- 4 poles electrical motor (1450 RPM) with thermal protection and water cooling.
- Three ceramic pistons, Nickel plating brass linear pump head with high temperature water seals and bushing.
- Integrated elastic joint, for best pump coupling
- Low voltage and delayed Total Stop.
- Suction and delivery S. S. valves.
- Integrated detergent suction with external suction probe.
- Pressure regulator.
- Glycerine pressure gauge.
- Galvanized steel frame.
- Stainless Steel covers.



Integrated elastic joint, for best pump coupling

STANDARD EQUIPMENT

- 3.700.0030 Gun M22 - 3/8" with rotating coupling



- 3.701.0027 Lance M22 high/low pressure



- 3.103.0050 Nozzle type 045 (mod. 2015 LP)
- 3.103.0055 Nozzle type 070 (mod. 2021 LP)
- 3.103.0049 Nozzle type 040 (mod. 2515 LP)



- 4.618.0143 High pressure hose 10 m



- Power cable 5 m

Optional:

- 0.966.0108 Kit hose reel with hose R2-5/16" 15 m. included for KCR 2015-2515
- 0.966.0107 Kit hose reel with hose R2-3/8" 15 m. included for KCR 2021
- 6.602.0040 Turbo Lance (2015-2515)
- 6.602.0042 Turbo Lance (2021)
- 6.602.0027 Sandblasting lance (2015-2515)
- 6.602.0029 Sandblasting lance (2021)

	KCR 2015 LP	KCR 2021 LP	KCR 2515 LP
code	8.674.0006	8.674.0011	8.674.0010
operat. pressure/max	200 bar-2900 psi	200 bar-2900 psi	250 bar-3600 psi
delivery rate	900 l/h-3.96 GPM	1260 l/h-5.55 GPM	900 l/h-3.96 GPM
abs. power/voltage	7000W - 400/415V~50Hz 3 ph	9400W - 400/415V~50Hz 3 ph	8500W - 400V~50Hz 3 ph
motor/pump type/RPM	MPWJ5 Ni/1450 RPM	MPWJ5 Ni/1450 RPM	MPWJ5 Ni/1450 RPM
max. water inlet temperature	60 °C	60 °C	60 °C
dimension/weight	50x90x83cm/56 kg - 123 lbs	50x90x83cm/58 Kg - 128 lbs	50x90x83cm / 59 kg - 130 lbs